

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°53'30" W., bet. secs. 2 and 35. Across Rye Patch Reservoir.
10.00	Waters edge, Rye Patch Reservoir, bears NE. and SW; over nearly level ground.
10.25	Record distance for the 1974 witness point; there is no remaining evidence of the position of the corner. This point serves no further function.
13.893	Point for a witness point, at intersection with the 4144 foot contour line, on the west side of Rye Patch Reservoir. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> WP T33N R32E S35 <hr/> S 4144 FT 2 T32N 2010 </div>
40.058	The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the N. bdy., T. 32 N., R. 32 E., executed under Group No. 498. <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.H. Dyer in 1863, and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor D.R. Garoutte in 1974</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside.</p> <p>N. 0°07'30" W., bet. secs. 23 and 24.</p> <p>Over nearly level land, through greasewood.</p>
20.033	Point for the N 1/16 sec. cor. of secs. 23 and 24. POINT NOT MONUMENTED