

DEPENDENT RESURVEY OF A PORTION OF THE PRESENT CALIFORNIA-NEVADA
STATE LINE FROM WITNESS MILE POST NO. 52 1/2 TO MILE POST NO. 60

CHAINS	
	<p>T. 38 N., R. 17 E., executed under Group No. 35, California, and an embedded mound of stone, 4 ft. base, 6 ins. high, NW. of cor. Corner is located 2 lks. E. of the corner of fences extending S. and W.</p>
	<p>Continue along fence.</p>
33.547	<p>Point for the 1/4 sec. cor. of sec. 32, T. 38 N., R. 18 E., hereinafter described.</p>
36.453	<p>A position determined for the N 1/16 sec. cor. of sec. 26, on the E. bdy. of T. 38 N., R. 17 E., California, by Conn Davis, California Professional Land Surveyor No. 6508, monumented with an aluminum post, 2 ins. diam., firmly set, projecting 17 ins. above the ground, with aluminum cap mkd. CLD SURVEYING S26 1/16 + LS 6508, as recorded in Lassen County, California, Book 37 of Maps, Page 98, filed as Document No. 2002-08897. Corner is located at the corner of fences extending N. and W.</p>
56.233	<p>A position determined for the 1/4 sec. cor. of sec. 26, on the E. bdy. of T. 38 N., R. 17 E., California, by Conn Davis, California Professional Land Surveyor No. 6508, monumented with an aluminum rod, 3/4 in. diam., firmly set, projecting 16 ins. above ground, with aluminum cap mkd. CLD SURVEYING E 1/4 LS 6508, as recorded in Lassen County, California, Book 37 of Maps, Page 98, filed as Document No. 2002-08897.</p>
74.081	<p>Point for the closing cor. of Tps. 37 and 38 N., R. 18 E., hereinafter described.</p>
76.018	<p>From this point, a position determined for the S 1/16 sec. cor. of sec. 26, on the E. bdy. of T. 38 N., R. 17 E., California, by Conn Davis, California Professional Land Surveyor No. 6508, monumented with an aluminum rod, 3/4 in. diam., firmly set, projecting 14 ins. above ground, with aluminum cap mkd. CLD SURVEYING 1/16 LS 6508, as recorded in Lassen County, California, Book 37 of Maps, Page 98, filed as Document No. 2002-08897, bears WEST, 0.030 chs. dist.</p>
79.340	<p>Mile Post No. 60, monumented with a wood post, 6x6 ins., firmly set, projecting 32 ins. above a mound of stone, 6 ft. base, 2 1/2 feet high, mkd. 60 M on the N. face, NEV on the E. face and CAL on the W. face, from which the original bearing object</p> <p style="padding-left: 40px;">A basalt rock, 4x3x3 ft. above ground, bears S. 72 1/2° E., 11 lks. dist., mkd. N.</p>
	<hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 38 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor G.W. Garside in 1880 and a Portion of the Resurvey Executed by U.S. Surveyor H.W. Reppert and U.S. Transitman L.R. Mercer in 1917</p> <hr/>
	<p>From the cor. of secs. 32 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above a mound of stone, 5 ft. base, 2 ft. high, with brass cap mkd. as described</p>