

DEPENDENT RESURVEY OF THE FOURTH STANDARD PARALLEL SOUTH THROUGH
A PORTION OF RANGE 54 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">SC T16S R53E R54E <u>S36 S31</u></p> <p style="text-align: center;">2011</p> <p>Deposit mkd. stone alongside the stainless steel post.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE FOURTH STANDARD PARALLEL SOUTH THROUGH RANGE 53 EAST, MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Deputy Surveyor E.A. Carter in 1881</p> <hr/> <p>From the standard cor. of Tps. 16 S., Rs. 53 and 54 E., hereinbefore described.</p> <p>N. 89°36'00" W., on the S. bdy. of sec. 36.</p>
23.20	Ridge, bears N. and S.
40.628	<p>The standard 1/4 sec. cor. of sec. 36 , T. 16 S., R. 53 E., perpetuated by Dona J. Rogers, Nevada Professional Land Surveyor No. 11192, monumented with a U.S. Dept. of Agriculture Forest Service aluminum post, 2 1/2 ins. diam., set in a mound of stone, 3 ft. base, 1 ft. high, with aluminum cap mkd. T16S R53E 1/4 S36 SC 1995, with a granite stone, 18x12x7 ins., mkd. 1/4 on a face, alongside aluminum post, as described in Humboldt- Toiyabe National Forest Field Book for Mount Stirling, Page 3, and recorded on USDA Forest Service Form 7100-52 Corner Record, NV21_T0160S R0530E_640100_1995, dated 6/09/1995.</p> <p>Add the mks. 2011 to aluminum cap and rebuild the mound of stone, 4 ft. base, to top.</p> <hr/> <p>S. 89°51'10" W., beginning new measurement.</p>
28.30	Trail road, 15 lks. wide, bears N. 20° E. and S. 20° W.
31.90	Ravine, drains NE.
34.186	<p>From this point, the closing cor. of secs. 1 and 2, T. 17 S., R. 53 E., bears NORTH, 0.030 chs. dist., monumented with a granite stone, 20x10x8 ins., set in a mound of stone, 3 ft. base, 1 ft. high, mkd. with 1 groove on the E. face, 5 grooves on the W. face and CC on the N. face. Rebuild the mound of stone, 4 ft. base.</p>