

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 18 S., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T18S R51E 1/4 S 6   S 5</p> <p style="text-align: center;">2007</p> <p>Insert rebar inside stainless steel post.</p> <hr/> <p>N. 0°00'40" W., beginning new measurement.</p>
40.859	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set in a collar of stone, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the S. bdy. of T. 17 S., R. 51 E., executed under Group No. 433.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 17, T. 18 S., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
10.60	<p>From the 1/4 sec. cor. of secs. 17 and 20.</p> <p>N. 0°37'50" E., on the N-S center line of sec. 17.</p> <p>Over nearly level land, through scattered sagebrush.</p> <p>Graveled road, 38 lks. wide, bears S. 20° E and N. 20° W.</p>
40.450	<p>Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T18S R51E C 1/4 S17</p> <p style="text-align: center;">2007</p>
80.895	<p>The 1/4 sec. cor. of secs. 8 and 17.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 16 and 17.</p> <p>S. 87°10'20" W., on the E-W center line of sec. 17.</p> <p>Over nearly level land, through scattered sagebrush.</p>