DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH THROUGH RANGE 51 EAST, MOUNT DIABLO MERIDIAN, NEVADA

MOUNT DIABLO MERIDIAN, NEVADA	
CHAINS	Reestablishment of the Survey Executed by E.L. Bridges in 1879
	Beginning at the standard cor. of Tps. 26 N., Rs. 51 and 52 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fifth Standard Parallel North, through Range 51 East, executed under Group No. 201.
	N. 89°43'20" W., on the S. bdy. of sec. 36.
19.50	Crest of hill, bears N. and S.
39.841	Point for the standard 1/4 sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top with brass cap mkd.
	SC T26N R51E 1/4 S36
	2012
75.80	Barbed wire fence, bears S. 30° E. and N. 30° W.
79.682	The standard cor. of secs. 35 and 36, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, 14 ins. in the ground, in a partially embedded mound of stone, 4 ft. base. This is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	SC T26N R51E S35 S36
	2012
	Bury rebar alongside the stainless steel post.
	N. 89°38'30" W., on S. bdy. of sec. 35.
39.466	The standard 1/4 sec. cor. of sec. 35, perpetuated by person(s) unknown, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, 14 ins. in the ground, with a volcanic stone, 12x8x4 ins., mkd. 1/4 on a face, loosely set alongside, within an embedded mound of stone, 3 ft. base.