DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 26 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

T. 26 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA	
CHAINS	N 1/16 S 1 S 6
	2012
80.428	The cor. of Tps. 26 and 27 N., Rs. 50 and 51 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 27 N., R. 50 E., executed under Group No. 145.
	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 26 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of a Portion of the Survey Executed by E.L. Bridges in 1879
	From the standard cor. of secs. 31 and 32, hereinbefore described.
	N. 0°38'50" E., bet. secs. 31 and 32.
37.30	Barbed wire fence, bears S. 70° E. and N. 70° W.
37.80	Power transmission line, bears S. 75° E. and N. 75° W.
38.90	J.D. Ranch Road, improved dirt surface, 30 lks. wide, bears S. 80° E. and N. 75° W.
40.095	Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set a nail, 12 ins. long, 1/4 in. diam. shank, 1/2 in. diam. head, 24 ins. below the surface of the ground.
	from which
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground, for a reference monument, bears S. 43°50" E., 410.3 lks. dist., with brass cap mkd. RM 1/4 S32 270.8 FT TO COR 2012, and an arrow pointing to the corner.
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 46°25" W., 285.3 lks. dist., with brass cap mkd. RM 1/4 S31 188.3 FT TO COR 2012, and an arrow pointing to the corner.
74.90	Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.
80.190	Point for the cor. of secs. 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.