

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUDARY,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of a Portion of the Survey Executed
by U.S. Deputy Surveyors H.E. Franks and J.S. Mullen in 1904,
and a Portion of the Dependent Resurvey Executed by
Cadastral Surveyor L.A. Barney and Surveying Technician
M.G. Petrosine in 2009-11

From the witness E 1/16 sec. cor. of secs. 1 and 36, monumented
with a stainless steel post, 2 1/2 ins. diam., firmly set,
projecting 4 ins. above the ground, with brass cap mkd. as
described in the field notes of the dependent resurvey of the a
portion of the south boundary, T.13 N., R. 28 E., executed under
Group No. 878.

N. 89°57'50" W., bet. secs. 1 and 36.

Across level land, covered with shadescale, cheat and
bunchgrass.

- 0.20 Left bank of the Walker River, bears NW. and S., thence across
river, course S.
- 0.948 True point for the E 1/16 sec. cor. of secs. 1 and 36, at
proportionate dist., falls in the Walker River where a permanent
monument cannot be established.
- 1.50 Right bank of the Walker River, bears NW. and S., continue
across level land.
- 10.951 The E-W 1/64 sec. cor. of secs. 1 and 36, monumented with an
aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins.
above the ground, with aluminum cap mkd. as described in the
dependent resurvey of a portion of the south boundary, T.13 N.,
R. 28 E., executed under Group No. 635.

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
U.S. Deputy Surveyors H.E. Franks and J.S. Mullen in 1904

From the cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the
Tp., monumented with the lower portion of a concrete filled iron
post, 2 ins. diam., 24 ins. long, recovered 6 ins. below the
surface of lawn covered ground, with the upper portion found
laying alongside, with brass cap mkd. as described in the
dependent resurvey of a portion of the S. bdy. of Tp. 13 N.,
R. 28 E., executed under Group No. 66.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
6 ins. below the surface of the lawn covered ground, over a
plastic-encased magnet, with brass cap mkd.