

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 38 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS | Reestablishment of a Portion of the Survey Executed by U. S. Deputy Surveyor G.W. Garside in 1874 | | | | | | | | | | |
|--------|---|------|------|-----|-----|-----|-----|------|--|------|--|
| | <p>Beginning at the cor. of secs. 1, 2, 35 and 36, monumented with a trap stone, 10x8x6 ins., loosely set in a small mound of stone, plainly mkd. with 1 notch on E. edge and 5 notches on W. edge, (Record, charred post), with a steel fence post alongside, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T38N</td><td>R31E</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">T37N</td></tr> </table> <p>2001</p> </div> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>From this cor., National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) station "ROBERTS", bears N. 79°51'50" E. (mean bearing), 520.820 chs. dist., monumented with a standard brass tablet cemented in solid rock, mkd. ROBERTS 1965.</p> <p>S. 87°16'30" W., bet. secs. 2 and 35.</p> <p>Over nearly level terrain.</p> | T38N | R31E | S35 | S36 | S 2 | S 1 | T37N | | | |
| T38N | R31E | | | | | | | | | | |
| S35 | S36 | | | | | | | | | | |
| S 2 | S 1 | | | | | | | | | | |
| T37N | | | | | | | | | | | |
| 36.50 | Shawnee Creek, 10 lks. wide, course NE. | | | | | | | | | | |
| 42.150 | <p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T38N</td><td>R31E</td></tr> <tr><td>S35</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td colspan="2">T37N</td></tr> </table> <p>2001</p> </div> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> | T38N | R31E | S35 | | 1/4 | — | S 2 | | T37N | |
| T38N | R31E | | | | | | | | | | |
| S35 | | | | | | | | | | | |
| 1/4 | — | | | | | | | | | | |
| S 2 | | | | | | | | | | | |
| T37N | | | | | | | | | | | |
| 51.70 | Trail road, 18 lks. wide, bears NE. and SW. | | | | | | | | | | |
| 84.300 | Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. | | | | | | | | | | |