## DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 37 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 37 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	
	T37N R19E R20E
	S12
	S 7
	2000
	Bury the original cornerstone alongside stainless steel post.
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.
	DEPENENT RESURVEY OF PORTIONS OF THE WEST BOUNDARY, T. 37 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of Portions of the Survey Executed by U.S. Deputy Surveyor G.W. Garside in 1880, Portions of the Dependent Resurvey Executed by U.S. Surveyor H.W. Reppert and U.S. Transitman L.R. Mercer in 1917 and the Dependent Resurvey Executed by Cadastral Surveyor N.R. Forsyth in 1973
	From the 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 37 N., R. 18 E., executed under Group No. 52.
	From this cor., the corner of wire fences extending S. and W. bears S. 33°07' W., 1.10 chs. dist.
	From this same cor., a position established by person(s) unknown, bears N. 10°17'50" W., 6.290 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 12 ins. above the ground, with a trapstone, 14x12x6 ins., laying loose alongside, plainly mkd. 1/4 WC.
	N. 0°15'10" W., bet. secs. 31 and 36.
	Over dry bed of Duck Lake.
20.157	Point for the N 1/16 sec. cor. of secs. 31 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	N 1/16 S36 S31
	2000
40.314	The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 37 N., R. 18 E., executed under Group No. 52, with a steel fence post alongside.