

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 37 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T38N R19E S31 1/4 ——— S 6 T37N 2000
42.10	Gravel road, 36 lks. wide, bears N. 70° E. and S. 70° W.
80.758	The cor. of Tps. 37 and 38 N., Rs. 18 and 19 E., monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N. bdy. of T. 37 N., R. 18 E., executed under Group No. 502.
<hr/> DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 37 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/> Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor G.W. Garside in 1880, and a Portion of the Dependent Resurvey Executed by U.S. Cadastral Engineer E. Voigt in 1922 <hr/> From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described. N. 0°18'50" W., bet. secs. 35 and 36. Over rolling terrain.	
41.231	Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T37N R19E 1/4 S35 S36 2000
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
56.20	Wire fence, bears S. 60° E. and N. 60° W.
75.50	Wire fence, bears N. 22° E. and S. 22° W.
82.462	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.