

DEPENDENT RESURVEY OF PORTIONS OF THE NORTH BOUNDARY,
T. 26 N., R. 48 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A PK nail, 2 ins. long, 3/8 in. diam., set in a drill hole in the concrete apron on E. side of truck maintenance building, for a reference monument, bears S. 21°54' W., 39.4 lks. dist.</p> <p>A PK nail, 2 ins. long, 3/8 in. diam., set in a drill hole in the concrete apron on E. side of truck maintenance building, for a reference monument, bears N. 44°00' W., 50.9 lks. dist.</p> <p>Point falls in active mining area.</p> <p>From this point, the cor. of secs. 1, 6, 7 and 12, Tps. 26 N., Rs. 47 and 48 E., bears S. 1°06'40" W., 79.994 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 26 N., R. 47 E., executed under Group No. 92.</p> <p>From this same point, United States Coast and Geodetic Survey benchmark "W 76" bears S. 33°07'30" W., 33.765 chs. dist., monumented with standard brass cap, 3 1/2 ins. diam., firmly cemented into a drill hole in a rock outcrop, with top mkd. W 76 1934.</p> <p>From this same point, an Apex Surveying and Mapping control point bears S. 50°43'30" E., 90.061 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with plastic cap mkd. APEX CONTROL POINT, with a steel fence post, projecting 3 ft. above the ground, alongside.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, T. 27 N., R. 48 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors A.J. Hatch and J.H. Eaton in 1869</p> <hr/> <p>From the cor. of Tps. 26 and 27 N., Rs. 47 and 48 E., hereinbefore described.</p> <p>N. 1°00'20" E., bet. secs. 31 and 36.</p> <p>Over rolling to mountainous terrain.</p> <p>39.993 Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner. Point falls in large active mining area where it is impractical to set a permanent monument.</p> <p>79.986 Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	--