

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 5003 A,
T. 27 N., R. 48 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, the true point for Cor. No. 2, Mineral Survey No. 5003 A, cancelled NEE 31 lode, identical with Cor. No. 2, Mineral Survey No. 5003 B, cancelled M.1001 millsite bears N. 86°00'00" E., 22.720 chs. dist.</p> <p>From the true point for Cor. No. 2, Mineral Survey No. 5003 A, cancelled NEE 31 lode, identical with Cor. No. 2, Mineral Survey No. 5003 B, cancelled M.1001 millsite, the witness corner for Cor. No. 2, Mineral Survey No. 5003 A, cancelled NEE 31 lode, identical with Cor. No. 2, Mineral Survey No. 5003 B, cancelled M.1001 millsite, monumented with iron post, 1 in. diam., firmly set, projecting 13 ins. above the ground, with brass cap, 2 ins. diam., mkd. W/C N31 2 USMS 5003A W/C M1001 2 USMS 5003 B, with a wood post 4x4 ins., 40 ins. long, lying loosely alongside, with aluminum tags mkd. W/C NE COR 31 W/C NW COR 1001, bears N. 4°03'40" W., 0.349 chs. dist.</p>
	<p>Thence S. 86°00'00" W., on line 1-2, Mineral Survey No. 5003 A, NEE 32 lode.</p>
0.282	Intersect the line bet. secs. 33 and 34, at a point from which the true point for 1/4 sec. cor. of sec. 33 only, bears S. 2°46'00" W., 3.666 chs. dist., hereinbefore described.
22.720	Cor. No. 2, Mineral Survey No. 5003 A, NEE 32 lode, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap, 2 ins. diam., mkd. N32 2 USMS 5003 A, with a wood post, 4x4 ins., projecting 3 1/2 ft. above the ground, 4 1/2 lks. E. of the iron post.
<p>SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 27 N., R. 48 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	<p>From the cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°00'40" W., bet. secs. 34 and 35.</p> <p>Over steep mountainous terrain.</p>
16.70	Ridge, bears N. 65° E. and S. 65° W.
33.30	Creek, 2 lks. wide, course N. 60° E.
37.50	Road, 15 lks. wide, bears N. 50° E. and S. 50° W.
40.000	Point for the 1/4 sec. cor. of secs. 34 and 35.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T27N R48E 1/4 S34 S35 2010</p>