

## TOWNSHIP 24 SOUTH, RANGE 58 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The June 5, 2012 mean magnetic declination was determined to be 12°14' E. as obtained from the National Oceanic and Atmospheric Administration National Geophysical Data Center declination calculator.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA.</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors J.M. Brunt and W.H. Proctor in 1881 under Contract No. 115.</p> <hr/> <p>Beginning at the cor. of secs. 25, 30, 31 and 36, perpetuated by Gilbert D. Buck, Nevada Professional Land Surveyor No. 3393, monumented with an unrecorded rebar, 5/8 in. diam., firmly set flush with the ground, with an aluminum cap, with the original limestone, 19x12x6 ins. (Record: sandstone, 22x14x8 ins.), with 1 notch on the south side, lying alongside rebar. This position was adopted by Joseph P. Fielding, Nevada Professional Land Surveyor No. 6199, in 1991, as recorded in Clark County, Nevada, File 60, Page 95, of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table border="1" data-bbox="876 1144 1023 1291"> <tr><td colspan="2">T24S</td></tr> <tr><td>R58E</td><td>R59E</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S36</td><td>S31</td></tr> </table> <p>2013</p> <p>Insert the rebar inside the stainless steel post and deposit the mkd. stone alongside.</p> <p>N. 0°20'20" E., bet secs. 25 and 30.</p> <p>Gradual ascent, over rolling land with creosote and cacti.</p> <p>32.10 Power transmission line, bears S. 60 E. and N. 60 W.</p> <p>41.272 The 1/4 sec. cor. of secs. 25 and 30, perpetuated by Joseph P. Fielding, Nevada Professional Land Surveyor No. 6199, monumented with a rebar, 5/8 in. diam., firmly set flush with the ground, with an aluminum cap, with the original limestone, 19x10x5 ins. (Record: sandstone, 21x14x8 ins.) mkd. 1/4 on one face, lying alongside, as recorded in Clark County, Nevada, File 60, Page 95 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p>	T24S		R58E	R59E	S25	S30	<hr/>		S36	S31
T24S											
R58E	R59E										
S25	S30										
<hr/>											
S36	S31										