DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH THROUGH A PORTION OF RANGE 51 EAST, MOUNT DIABLO MERIDIAN, NEVADA

	MOUNT DIABLO MEKIDIAN, NEVADA
CHAINS	
20.215	The standard 1/4 sec. cor. of sec. 31, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fifth Standard Parallel North through Range 51 East, executed under Group No. 918.
	S. 89°47'20" W., beginning new measurement.
10.95	Dry creek, 10 lks. wide, drains N.
19.65	Barbed wire fence, bears N. 10° E. and S. 10° W.
25.633	The closing cor. of Tps. 25 N., Rs. 50 and 51 E., hereinafter described.
29.75	Dirt road, 20 lks. wide, bears N. 5° E. and S. 5° W.
37.05	Barbed wire fence, bears S. 60° E. and N. 60° W.
40.430	The standard cor. of Tps. 26 N., Rs. 50 and 51 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fifth Standard Parallel North through Range 51 East, executed under Group No. 918.
	DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 25 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by U.S. Deputy Surveyor D.H. Barker in 1879
	From the cor. of Tps. 24 and 25 N., Rs. 50 and 51 E., determined at a squared wood post, 4x5x60 ins., lying loose on the ground, with no discernible markings. This is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T25N R50E R51E S36 S31 S 1 S 6 T24N
	2013
	Bury the wood post alongside the stainless steel post.
	N. 0°43'20" E., bet. secs. 31 and 36.