

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 25 N., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.L. Bridges in 1879</p>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°13'20" E., bet. secs. 35 and 36.</p> <p>Over rolling land, with sagebrush and rabbit brush.</p>
1.30	Enter Garden Valley, edge bears NE. and SW.
14.30	Barbed wire fence, bears NE. and SW.
19.930	<p>Point for the S 1/16 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 1/16 S35 S36</p> <p>2013</p> </div>
39.860	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R50E 1/4 S35 S36</p> <p>2013</p> </div>
71.00	Trail road, 15 lks. wide, bears E. and W.
75.30	Enter grassy meadow, bears NE. and SW.
79.720	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R50E S26 S25 S35 S36</p> <p>2013</p> </div>