

DEPENDENT RESURVEY OF THE FIRST STANDARD PARALLEL NORTH  
THROUGH A PORTION OF RANGE 40 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors J.R. Glover and G.H. Perrin in 1880 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor D.A. Crain in 1959</p> <hr/>
	<p>Beginning at the standard 1/4 sec. cor. of sec. 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the First Standard Parallel North through R. 40 E., executed under Group No. 385.</p>
	<p>N. 89°45'50" W., on the S. bdy. of sec. 32.</p>
5.77	Trail road, 12 lks. wide, bears N. 30° E. and S. 20° W.
31.40	Spur, slopes N.
32.189	Intersect line 1-2, Mineral Survey No. 4414, Golden Eagle lode, at a point from which Cor. No. 1, identical with Cor. No. 1, Mineral Survey No. 4414, Little Bill lode, hereinafter described, bears N. 72°13'00" W., 3.751 chs. dist.
32.271	The closing cor. of secs. 5 and 6, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above a mound of stone, 5 1/2 ft. base, 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the of the First Standard Parallel North through R. 40 E., executed under Group No. 385.
38.536	The standard cor. of secs. 31 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above a mound of stone, 6 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the First Standard Parallel North through R. 40 E., executed under Group No. 385.
	<hr/> <p>N. 88°17'40" W., on the S. bdy. of sec. 31.</p>
7.267	Intersect line 2-3, Mineral Survey No. 4414, Little Bill lode, at a point from which Cor. No. 2, hereinafter described, bears N. 20°35'00" E., 3.931 chs. dist.
9.23	Spur, slopes N. 20° W.
15.68	Wash, drains N. 35° W.
42.262	The standard 1/4 sec. cor. of sec. 31, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above a mound of stone, 5 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the First Standard Parallel North through R. 40 E., executed under Group No. 385.
	<hr/>