DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 7 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 20.674

The 1/4 sec. cor. of secs. 4 and 5, perpetuated by R.L. Hafen, Nevada Professional Land Surveyor No. 4428, monumented with an unrecorded rebar, 1/2 in. diam., firmly set, projecting 1 in. above the ground, in a mound of stone, 2 1/2 ft. base, 10 ins. high, with an aluminum cap, 2 ins. diam., mkd. R. L. HAFEN PLS 4428, with a trachyte stone, 17x10x6 ins. (record, 14x12x8 ins.), loosely set alongside, mkd. 1/4 on W. face. This is accepted as a careful and faithful perpetuation of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T7S R61E 1/4 S 5|S 4

2015

Insert the rebar inside the stainless steel post and bury the mkd. stone alongside.

From this cor., a cor. of barbed wire fences bears N., 2 lks. dist., with fences extending N. and W.

SUBDIVSION OF SECTION 5,
T. 7 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

From the 1/4 sec. cor. of secs. 5 and 8, monumented with a PK magnetic nail, firmly set in a divot in the pavement, 1/2 in. below the surface. Cor. is located in the asphalt surfaced parking lot of Pahranagat High School, as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 7 S., R. 61 E., executed under Group No. 851.

from which

The SW. cor. of a cinder block building, 13 ft. high, bears S. 17°16' E., 29.8 lks. dist.

An "x", 2x2 ins., mkd. on a horizontal cement step, bears N. $76^{\circ}16^{\circ}$ W., 84.2 lks. dist.

An "x", 2x2 ins., mkd. on a horizontal cement pad, bears N. $3^{\circ}25^{\circ}$ W., 19.6 lks. dist.

N. 0°17'20" E., on the N-S center line of sec. 5.

Through a portion of the Alamo Townsite, Lincoln County, Nevada.

51 | Point for the C-S 1/16 sec. cor. of sec. 5.

POINT NOT MONUMENTED

20.551