

TOWNSHIP 6 SOUTH, RANGE 61 EAST, MOUNT DIABLO MERIDIAN, NEVADA

| | | | | | | | | | | | | | |
|----------|--|----------|--|-----|-----|--|--|-----|-----|-----|--|------|--|
| CHAINS | <p>The mean magnetic declination is 15 1/2°, as shown on U.S.G.S. 7 1/2 minute quadrangle map "ASH SPRINGS, NEV" dated 1969.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.B. Monroe in 1870</p> <hr/> <p>Beginning at the cor. of secs. 4, 5, 32 and 33, perpetuated by Richard L. Hafen, Nevada Professional Land Surveyor No. 4428, in 1983, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, flush with the ground, in a mound of stone, 3 ft. base, 2 1/2 ft. high, with an aluminum cap, 2 ins. diam., mkd. R.L. Hafen PLS 4428, with a trachyte stone, 18x12x8 ins. (Record: 10x10x8 ins.), lying loose in the mound of stone, mkd. with 2 notches on one edge and 4 notches on an adjacent edge, with a steel fence post set alongside, projecting 4 ft. above the ground, as recorded in Lincoln County, Nevada, Parcel Map, Plat Book A, Page 198, File No. 77005.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T6S R61E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S32</td><td style="padding: 0 5px;">S33</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; height: 5px;"></td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 5</td><td style="padding: 0 5px;">S 4</td></tr> <tr><td colspan="2" style="text-align: center;">T7S</td></tr> <tr><td colspan="2" style="text-align: center;">2014</td></tr> </table> </div> <p>Insert rebar inside and bury mkd. stone alongside stainless steel post.</p> <p>Cor. is located in a barbed wire fence, bears E. and W.</p> <p>N. 88°43'20" W., bet. secs. 5 and 32.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p> <p>19.65 U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears N. and S.</p> <p>Thence over cultivated land.</p> <p>39.218 The 1/4 sec. cor. of secs. 5 and 32, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 2001, monumented with an ash post, 3 ins. diam., 32 ins. long, firmly set, projecting 9 ins. above the ground, with a rebar, 5/8 in.</p> | T6S R61E | | S32 | S33 | | | S 5 | S 4 | T7S | | 2014 | |
| T6S R61E | | | | | | | | | | | | | |
| S32 | S33 | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| S 5 | S 4 | | | | | | | | | | | | |
| T7S | | | | | | | | | | | | | |
| 2014 | | | | | | | | | | | | | |