

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S. 87°36'10" W., bet. secs. 20 and 29.</p> <p>Over rolling terrain, through scattered sagebrush and bunch grass.</p>
37.133	<p>The 1/4 sec. cor. of secs. 20 and 29, perpetuated by Richard L. Hafen, Nevada Professional Land Surveyor No. 4428, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, flush with the surface of the ground, in a mound of stone, 3 ft. base, 1 ft. high, with an aluminum cap mkd. R.L. Hafen PLS 4428, with a trachyte stone 18x9x5 ins. (Record: 10x8x8 ins.), lying loose in a mound of stone, dimly mkd. 1/4 on a face, with a steel fence post set alongside, projecting 3 ft. above the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T6S R61E S20 1/4 — S29</p> <p style="text-align: center;">2014</p>
	<p>Insert rebar inside and bury the mkd. stone alongside stainless steel post. Reset steel fence post, 3 ft. high alongside mound of stone.</p>
	<p>Cor. is located in a barbed wire fence, bears E. and W.</p>
	<p style="text-align: center;">_____</p> <p>N. 88°34'10" W., beginning new measurement.</p>
20.30	<p>U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 17° E. and N. 17° W.</p>
41.40	<p>Richardville Road, asphalt surfaced, 30 lks. wide, bears S. 2° E. and N. 2° W.</p>
43.324	<p>The cor. of secs. 19, 20, 29 and 30.</p>
	<p style="text-align: center;">SUBDIVISION OF SECTION 29, T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>From the 1/4 sec. cor. of secs. 29 and 32.</p>
	<p>N. 1°30'20" E., on the N-S center line of sec. 29.</p>
	<p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
19.716	<p>Point for the C-S 1/16 sec. cor. of sec. 29.</p>