

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of a Portion of the Survey Executed by  
U.S. Deputy Surveyor E.B. Monroe in 1870

From the cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 16x12x10 ins. (Record: 12x9x7 ins.), firmly set, projecting 8 ins. above a mound of stone, 2 1/2 ft. base, 8 ins. high, mkd. with 5 notches on the S. edge and 1 notch on the E. edge.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

T4S R60E

S 2	S 1
-----	-----

S11	S12
-----	-----

2012

Bury the mkd. stone alongside stainless steel post.

N. 0°01'50" W., bet. secs. 1 and 2.

Over nearly level land, through scattered sagebrush.

5.40 Leave scattered sagebrush, enter nearly level farm land.

20.249 The S 1/16 sec. cor. of secs. 1 and 2, determined by Lenard D. Smith, Nevada Professional Land Surveyor No. 12751, in 2003, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, 6 ins. below the ground, with an aluminum cap, 2 ins. diam., mkd. L. Smith S 1/16 PLS 12751, as recorded in Lincoln County, Nevada, Record of Survey, Plat Book B, Page 498, File No. 120449. This is accepted as a careful and faithful determination of the position of the corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.

S 1/16

S 2	S 1
-----	-----

2012

Insert rebar inside stainless steel post.

Cor. is located in a cultivated field.

N. 0°01'50" W., beginning new measurement.