

SUBDIVISION OF SECTION 2,  
T. 4 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 89°42'50" E., on the computed E-W center line of the SE1/4 of the SW1/4 of the NE1/4 of sec. 2.
0.80	Power line, bears N. 15° E. and S. 15° W.
4.20	Gravel access road, 30 lks. wide, bears N. 40° E. and S. 40° W.
4.530	Point for Angle Point No. 5, of a metes-and-bounds survey in sec. 2, at the southeasterly edge of a gravel access road.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{c} S \ 2 \\ \text{SSN} \frac{\quad}{\quad} \text{SSN} \\ \text{AP} \ / \ 5 \end{array}$
	2013
4.966	The C-S-S-NE 1/256 sec. cor. of sec. 2, hereinbefore described.
	<hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEYS IN SECTION 2, T. 4 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	From Angle Point No. 1, on the E-W center line of the NE1/4 of sec. 2, hereinbefore described.
	N. 0°09'50" W., on line 1-2.
20.142	Angle Point No. 2, on the N. bdy. of sec. 2, hereinbefore described.
	From Angle point No. 3, on the N-S center line of the SE1/4 of the SW1/4 of the NE1/4 of sec. 2, hereinbefore described.
	N. 40°30'50" E., on line 3-4.
	Along the southeasterly edge of a gravel access road.
3.106	Point for Angle Point No. 4, of a metes-and-bounds survey.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$S \ 2 \ \left\{ \begin{array}{l} \text{AP} \ 4 \end{array} \right.$
	2013
	<hr/>
	N. 43°42'00" E., on line 4-5.