

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 14 S., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS
82.368

The cor. of secs. 1, 6, 7 and 12, perpetuated by person(s) unknown, monumented with an unrecorded 60d nail, firmly set, flush in the ground in the center of an embedded mound of stone, 3 ft. base, 6 ins. high. This nail and mound of stone correlate well with the position of the marked stone recovered by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1991, as recorded in Clark County, Nevada, File 58, Page 35 of Surveys, Document No. 910215, and is accepted as a careful and faithful perpetuation of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

| | |
|-------|------|
| T14S | |
| R69E | R70E |
| S 1 | S 6 |
| ----- | |
| S12 | S 7 |

2013

From this cor., a position reestablished as the cor. of secs. 1, 6, 7 and 12 by Kenneth C. Hamblin, Nevada Professional Land Surveyor No. 7276, in 1987, bears S. 45°39'10" E., 3.369 chs. dist., as recorded in Clark County, Nevada, File 46, Page 18 of Surveys, Document No. 870427. This same position was later utilized by Victor R. Campbell, Nevada Professional Land Surveyor No. 11424, in 2009, monumented with a rebar, 5/8 in. diam., projecting 1 in. above the ground, with a plastic cap mkd. "PLS 11424", as recorded in Clark County, Nevada, File 116, Page 59 of Parcel Maps, Document No. 20090313. This position was reestablished using a township corner established in an independent resurvey that has no relationship to the original survey and is not utilized during the course of this survey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
U.S. Deputy Surveyors R.H. Woods and W.H. Myrick in 1881

From the point for the cor. of secs. 23, 24, 25 and 26, at proportionate measurement latitudinally and at record departure from the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described, using the method of three point control as no evidence of the original survey could be found along the subdivisional lines to the W. or along the W. bdy. of the Tp.; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.