## DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 3 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

No. 120449. This is accepted as a careful and faithful reestablishment of the position of the cor. established in the 1958 dependent resurvey. This cor. will now refer to the SW cor. of sec. 36.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.

T3S R60E S36

2015

Insert rebar inside stainless steel post.

Continue measurement across sec. 1, T. 4 S., R. 60 E., on a blank line.

39.649

The cor. of secs. 1 and 2, T. 4 S., R. 60 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set 20 ins. below the surface of the ground, with brass cap mkd. as described in field notes of the dependent resurvey of a portion of the N. bdy. of T. 4 S., R. 60 E., executed under Group No. 914.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 3 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by Cartographic Aid D.A. Cannon Supervised by Cadastral Surveyor R.C. Yundt in 1958

From the SW sec. cor. of sec. 36.

N. 0°02'10" E., on the W. bdy. of sec. 36.

0.028

The closing cor. of secs. 1 and 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set 12 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N. bdy. of T. 4 S., R. 60 E., executed concurrently under this same Group.

From this cor., the cor. of secs. 1 and 2, T. 4 S., R. 60 E., bears N. 89°25'50" W., 0.680 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set 20 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N. bdy. of T. 4 S., R. 60 E., executed under Group No. 914.

Thence bet. secs. 35 and 36.