SUBDIVISION OF SECTION 36, T. 3 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 3 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	
20.480	A position determined as the SW 1/16 sec. cor. of sec. 36, by Lenard D. Smith, Nevada Professional Land Surveyor No. 12751, in 2003, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with an aluminum cap mkd. L. SMITH SW 1/16 PLS 12751, as recorded in Lincoln County, Nevada, Plat Book B, Page 498, File No. 120449. This position was determined based on an improper calculation of the C-S 1/16 sec. cor. of sec. 36, and is not utilized during the course of this survey.
20.932	Point for the SW $1/16$ sec. cor. of sec. 36, at intersection with the E-W center line of the SW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	SW 1/16 S36
	2015
40.907	The C-W 1/16 sec. cor. of sec. 36.
	From the point for the C-S 1/16 sec. cor. of sec. 36.
	N. 89°48'30" W., on the E-W center line of the SW1/4 of sec. 36.
19.984	The SW 1/16 sec. cor. of sec. 36.
39.968	The S 1/16 sec. cor. of secs. 35 and 36.
	METES-AND-BOUNDS SURVEY OF THE CENTERLINE OF NEVADA STATE ROUTE 318 THROUGH A PORTION OF SECTION 35, T. 3 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the point for the witness point at intersection of the centerline of Nevada State Route 318 with the N-S center line of the SE1/4 of sec. 35.
	Set a PK nail flush with the surface of the asphalt.
	from which
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 60°13'10" W., 151.1 lks. dist., with brass cap mkd. RM S35 99.7 ft. TO WP and an arrow pointing to the corner.
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 29°45'50" W., 151.3 lks. dist., with brass cap mkd. RM S35 99.9 ft. TO WP and an arrow pointing to the corner.