

DEPENDENT RESURVEY OF A PORTION
OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 32,
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	POINT NOT MONUMENTED
20.092	The C-W 1/16 sec. cor. of sec. 32, monumented with an iron post, 2 1/2 ins. diam. firmly set, projecting 8 ins. above a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the 1957 survey of the subdivision of section 32, T. 22 S., R. 60 E., executed under Group No. 357.
	S. 88°35'30" W., beginning new measurement.
3.10	Center of dirt road, 14 lks. wide, bears N. 5° E. and S. 5° W.
5.011	Point for the C-E-W-W 1/256 sec. cor. of sec. 32.
	POINT NOT MONUMENTED
10.022	Point for the C-W-W 1/64 sec. cor. of sec. 32.
	POINT NOT MONUMENTED
20.044	The 1/4 sec. cor. of secs. 31 and 32.
	FURTHER SUBDIVISION OF SECTION 32, T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the C-E 1/16 sec. cor. of sec. 32.
	N. 3°40'10" W., on the N-S center line of the NE1/4 of sec. 32.
	Over gently rolling land, through creosote and scattered yucca plants.
9.528	Point for the C-S-NE 1/64 sec. cor. of sec. 32.
	POINT NOT MONUMENTED
11.40	Center of dirt road, 14 lks. wide, bears N. 72° E. and S. 67° W.
19.056	The NE 1/16 sec. cor. of sec. 32, monumented with a rebar, no record found, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with an aluminum cap, 1 1/2 ins. diam., mkd. PLS 14195. This is accepted as a careful and faithful determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	NE 1/16 S32
	2014