

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by R.H. Woods and W.H. Myrick, U.S. Deputy Surveyors in 1881-82 and a Portion of the Dependent Resurvey Executed by B.R. Clifford, Cadastral Surveyor, in 1992-93.</p> <hr/> <p>Beginning at the witness cor. to the 1/4 sec. cor. of secs. 24 and 25, monumented with a brass tablet cemented in a limestone outcrop, with top mkd. WC T20S R62E S24 1/4 S25 1992 with an arrow pointing to the true point.</p> <p>Add the marks 2015 to the brass tablet.</p> <p>The witness cor. is located on the W. side of a spur at the east edge of a small foot trail. The brass tablet is set flush in the limestone outcrop and was covered with dirt and debris.</p> <p>S. 88°27'20" W., bet. secs. 24 and 25.</p> <p>Over steep mountainous terrain.</p> <p>7.399 True point for the 1/4 sec. cor. of secs. 24 and 25, determined at proportionate distance, located in a steep, unstable rock chute where it is impracticable to establish a permanent monument.</p> <p>46.163 The cor. of secs. 23, 24, 25 and 26, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T20S R62E S23 S24 S26 S25 1992.</p> <p>Add the marks 2015 to the brass cap.</p> <p>From this point, a rebar, 5/8 in. diam., firmly set, flush with the ground, with alum. cap. mkd. VTN ENGR 23 24 25 26 RLS 4046, as recorded in Clark County, Nevada, File 29, Page 31 of Surveys, bears N. 29°33'20" E., 2.335 chs. dist., not utilized during the course of this survey.</p> <p>From this same point, a rebar, 5/8 in. diam., firmly set, but leaning to the north, projecting 2 ins. above the ground, with alum. cap. mkd. NELSON E. MYER RLS 1871, bears N. 2°58'30" W., 2.058 chs. dist., not utilized during the course of this survey.</p>
40.135	<hr/> <p>N. 2°54'00" W., bet. secs. 23 and 24.</p> <p>Across a W. facing slope, over rugged limestone ridges and ravines.</p> <p>The 1/4 sec. cor. of secs. 23 and 24, as determined from reference monuments, and occupied by a rebar, 5/8 in. diam., firmly set 1 in. below the ground, with an unreadable alum. cap, as established by Frederick W. Organ, Nevada P.L.S. No. 4541, in 1993, as recorded in Clark County, Nevada, File 65, Page 49 of Surveys.</p> <p>from which</p>