

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 20 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
41.814	<p style="text-align: center;">S13 W 1/16 ——— S24</p> <p style="text-align: center;">2015</p> <p>This cor. is located on a steep easterly slope, of loose sand. The cor. of secs. 13, 14, 23 and 24.</p>
	<p style="text-align: center;">SUBDIVISION OF SECTION 24, T. 20 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the true point for the 1/4 sec. cor. of secs. 24 and 25. N. 0°42'50" W., on the N-S center line of sec. 24. Over steep, mountainous terrain.</p> <p>40.255 Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E-W center line, located on a nearly vertical limestone face where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the center 1/4 sec. cor., bears S. 86°45'20" W., 14.9 lks. dist. Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, over a magnet, with top mkd.</p> <p style="text-align: center;">WC T20S R62E C 1/4 S24 —————→ 2015</p> <p>from which</p> <p style="padding-left: 40px;">A rock outcrop, bears S. 33°49'50" E., 12.0 lks. dist., with BXO chiseled on it.</p> <p style="padding-left: 40px;">A steel pin, 18 ins. long, 3/4 in. diam., driven 14 ins. in a crack of limestone, bears N. 20°19'50" W., 14.0 lks. dist.</p>
60.385	<p>Point for the C-N 1/16 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>