

TOWNSHIP 19 SOUTH, RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The January 1, 2016 mean magnetic declination was determined to be 11°45' E., as obtained from the National Oceanic and Atmospheric Administration's National Geophysical Data Center declination calculator.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 19 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors, R.H. Woods and W.H. Myrick in 1881-1882 and a Portion of the Dependent Resurvey Executed by U.S. Cadastral Engineer, Carl S. Swanholm, in 1930-1933</p> <hr/> <p>Beginning at the cor. of secs. 25 and 36 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, during the dependent resurvey of the E. bdy., T. 19 S., R. 62 E., executed under Group No. 159, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T19S</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R62E</td><td style="padding: 0 5px;">T19S</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S25</td><td style="padding: 0 5px;">R63E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S36</td><td style="padding: 0 5px;">S30</td></tr> <tr><td colspan="2">1930</td></tr> </table> </div> <p>From this corner, a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. PLS 10160 RM 63.46 CNLV SURVEY MONUMENT, bears N. 46°40'30" E., 0.962 chs. dist.</p> <p>From this same corner, a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd. PLS 10160 58.58 53.87 CNLV SURVEY MONUMENT, bears S. 52°20'20" E., 0.887 chs. dist.</p> <p>From this same corner, a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd. PLS 10160 55.39 48.68 CNLV SURVEY MONUMENT, bears S. 46°42'10" W., 0.839 chs. dist.</p> <p>From this same corner, a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd. PLS 10160 RM 71.14 CNLV SURVEY MONUMENT, bears N. 52°20'00" W., 1.078 chs. dist.</p> <p>N. 0°32'00" W., along the E. bdy. of sec. 25.</p> <p>19.80      Old road, bears SE. and NNW.</p> <p>38.999     The 1/4 sec. cor. of sec. 30 only, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with a steel fence post set alongside, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines, T. 19. S., R. 63 E., executed under Group No. 159.</p>	T19S		R62E	T19S	S25	R63E	S36	S30	1930	
T19S											
R62E	T19S										
S25	R63E										
S36	S30										
1930											