

CORRECTIVE DEPENDENT RESURVEY  
OF A PORTION OF THE NORTH BOUNDARY,  
T. 15 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 40.572</p>	<p>The cor. of secs. 5, 6, 31 and 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above a mound of stone, 3 ft. diam., 1 ft. high, with an iron post, 1 in. diam., inverted alongside, projecting 2 ft., with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the south bdy., T. 14 S., R. 66 E., executed under Group No. 641.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 15 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors R.H. Woods and W.H. Myrick in 1881.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9, determined by Ernest H. Clary, Nevada Professional Land Surveyor No. 290, in 1963, monumented with a concrete cylinder, 6 ins. diam., 18 ins. long, buried 24 ins. below the surface of the ground, as recorded in Clark County, Nevada, File 12, Page 20, of Surveys, with a rebar of unknown origin, 5/8 in. diam., firmly set 12 ins. below the surface of the ground and above the concrete cylinder. This position has been accepted by adjacent landowners and professional land surveyors, is harmoniously related to existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R66E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 8</td> <td style="padding: 0 5px;">S 9</td> </tr> </table> <p>2015</p> </div> <p>Insert the rebar inside and bury the concrete cylinder alongside the stainless steel post.</p> <p>Corner is located in a cultivated field.</p> <p>N. 0°14'50" E., bet. secs. 4 and 5.</p> <p>4.00 Fence, bears SE. and NW.</p> <p>4.20 Improved farm access road, dirt surfaced, 30 lks. wide, parallels fence.</p> <p>4.75 Left bank of the Muddy River, course SE.</p> <p>5.70 Unimproved access road, dirt surfaced, 15 lks. wide, bears SE. and NW.; enter rolling land.</p>	S 5	S 4	S 8	S 9
S 5	S 4				
S 8	S 9				