

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment a Portion of the Survey Executed by U.S. Deputy Surveyors R.H. Woods and W.H. Myrick in 1881 and the Dependent Resurvey Executed by Cadastral Surveyor R.A. Zaninovich in 1994</p>
	<p>Beginning at the N 1/16 sec. cor. of secs. 7 and 8, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 15 S., R. 66 E., executed under Group No. 751, with a steel fence post set alongside.</p> <p>Cor. is located N., 20 lks. dist. of cliff.</p> <p>N. 0°37'30" W., bet. secs. 7 and 8.</p>
1.439	From this point, a rebar, 1 in. diam., firmly set, projecting 30 ins. above the ground, bears EAST, 0.303 chs. dist.
15.10	Base of spur, begin level river bottom.
21.20	Barbed wire fence, bears E. and W.
21.430	The cor. of secs. 5, 6, 7 and 8, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 6 ins. below the surface of dirt berm, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 15 S., R. 66 E., executed under Group No. 751.
	<hr/> <p>S. 88°30'50" W., bet. secs. 6 and 7.</p>
2.595	From this point, a NV Energy Settlement Monument, a brass cap, 3 1/2 ins. diam., set in a concrete cylinder, 8 1/2 ins. diam., projecting 11 ins. above sloping dirt berm, mkd. E-7 E-PONDS, bears NORTH, 0.206 chs. dist.
6.386	From this point, a NV Energy Settlement Monument, a brass cap, 3 1/2 ins. diam., set in a concrete cylinder, 8 1/2 ins. diam., projecting 9 1/2 ins. above sloping dirt berm, mkd. E-8 E-PONDS, bears NORTH, 0.216 chs. dist.
9.596	From this point, a NV Energy Settlement Monument, a brass cap, 3 1/2 ins. diam., set in a concrete cylinder, 8 1/2 ins. diam., projecting 25 ins. above sloping dirt berm, mkd. E-9 E-PONDS, bears NORTH, 0.275 chs. dist.
20.040	The E 1/16 sec. cor. of secs. 6 and 7, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 6 ins. below the surface of dirt berm, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 15 S., R. 66 E., executed under Group No. 751.