

DEPENDENT RESURVEY OF PORTIONS OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 7,
T. 15 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of a Portion of the Subdivision of Section 7 Executed by Cadastral Surveyor R.A. Zaninovich in 1994</p>
	<p>From the NE 1/16 sec. cor. of sec. 7, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 18 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the subdivision of section 7, T. 15 S., R. 66 E., executed under Group No. 751.</p> <p>Cor. is located N., 5 lks. dist. of a barbed wire fence, bears E. and W., E., 5 lks. dist. of a barbed wire fence, bears N. and S., and on the SW. edge of an ash dump.</p> <p>N. 0°27'00" W., on the N-S center line of the NE1/4 of sec. 7.</p>
6.71	Barbed wire fence, bears E. and W.
7.30	N. edge of ash dump.
7.926	Point for the C-N-S-N-NE 1/1024 sec. cor. of sec. 7.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">1/1024</p> <p style="text-align: center;">2016</p>
	Cor. is located on N. facing slope.
20.94	Barbed wire fence, bears E. and W.
21.136	The E 1/16 sec. cor. of secs. 6 and 7.
	<p>From the N 1/16 sec. cor. of secs. 7 and 8.</p> <p>S. 89°22'00" W., on the E-W center line of the NE1/4 of sec. 7.</p>
7.539	Point for the C-W-E-E-NE 1/1024 sec. cor. of sec. 7.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">1/1024</p> <p style="text-align: center;">2016</p>
	Cor. is located in a draw, drains S.
7.99	Corner of barbed wire fences extending S. and W.
8.90	Top of dirt berm, marking the E. edge of ash dump.
15.55	Barbed wire fence, bears NNE. and SSW.