THE FURTHER SUBDIVISION OF SECTION 7, T. 15 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 15 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	From the point for the C-S-S-NE-NE 1/1024 sec. cor. of sec. 7.
	S. 89°15'40" W., on the computed E-W center line of the SE1/4SW1/4NE1/4NE1/4 of sec. 7.
4.713	Point for a witness point on the E-W center line of the SE1/4SW1/4NE1/4NE1/4 of sec. 7.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	WP T15S R66E
	$s-s-n-n \xrightarrow{s/7} s-s-n-n$
	2016
	Cor. is located in a barbed wire, bears NNE. and SSW.
5.024	The point for the C-S-SW-NE-NE 1/1024 sec. cor. of sec. 7.
	From the point for the C-N-SW-NE-NE 1/1024 sec. cor. of sec. 7.
	S. 89°02'50" W., on the computed E-W center line of the NW1/4SW1/4NE1/4NE1/4 of sec. 7.
5.020	The C-N-S-N-NE 1/1024 sec. cor. of sec. 7.
	METES-AND-BOUNDS SURVEY IN SECTION 7, T. 15 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the witness point on the E-W center line of the SW1/4NE1/4NE1/4 of sec. 7, hereinbefore described.
	From this point, the point for the SW-NE-NE 1/256 sec. cor. of sec. 7, hereinbefore described, bears S. 89°09'10" W., 0.939 chs. dist.
	S. 11°37'30" E., on course adjacent to fence line, in sec. 7.
0.068	Point for Angle Point No. 1, in sec. 7.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.