

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 19 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°12'30" E., beginning new measurement.
14.054	The witness point at the intersection of a line parallel to and 400 feet southerly of the W1/2 mile bet. secs. 6 and 31, on the N. bdy. of the Tp., with the line bet. secs. 1 and 6, on the W. bdy. of the Tp., hereinafter described.
20.115	<p>The cor. of Tps. 18 and 19 S., Rs. 60 and 61 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the 1990 dependent resurvey of a portion of the west boundary, T. 19 S., R. 61 E., executed under Group No. 683.</p> <p>Add the marks 2015 to the brass cap.</p> <p>From this cor., an X etched into a metal plate, 3 x 5 ins., attached 3 1/2 ft. high on the easterly face of a power pole, bears S. 43°20' W., 1.476 chs. dist.</p> <p>From this same cor., a brass washer, 2 ins. diam., set in concrete, 8 ins. below the ground, bears S. 47°33'50" W., 1.461 chs. dist., mkd. CITY OF LAS VEGAS LV901NES.</p>
<hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 19 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors R.H. Woods and W.H. Myrick in 1881-82, a Portion of the Dependent Resurvey Executed by Cadastral Surveyor N.R. Forsyth in 1990 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor R.E. Williams in 1991</p> <hr/>	
	<p>From the cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above the ground, and in a collapsed mound of stone, with brass cap mkd. as described in the field notes of the 1991 dependent resurvey of a portion of the north boundary, executed under Group No. 697, with an aluminum washer, 2 ins. diam., mkd. NORTH LAS VEGAS 91 3NWS B.M. NO. NLV wired to it.</p>
	<p>Add the marks 2015 to the brass cap, and rebuild mound of stone, 4 ft. base to top.</p>
	<p>Cor. is located S., 6 lks. dist. of a wood post and cable fence, bears E. and W.</p>
	<p>N. 88°48'30" W., bet. secs. 4 and 33.</p>
	<p>Over gently rolling land.</p>
40.153	<p>The 1/4 sec. cor. of secs. 4 and 33, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the 1991 dependent resurvey of a portion of the north boundary, executed under Group No. 697.</p>