

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 7,
T. 19 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>An aluminum cap, 1 1/2 ins. diam., flush with the concrete of a curb, bears S. 27°51'50" E., 127.5 lks. dist., mkd. RM 84.15 PLS 8662.</p> <p>Cor. is located in the pavement near the N. edge of Horse Drive, bears E. and W.</p> <p>From this cor., a brass washer, 2 ins. diam., set in concrete of curb, bears S. 69°02'00" E., 1.547 chs. dist., mkd. NORTH LAS VEGAS NLV 917C4.</p> <p>N. 0°13'30" W., on the N-S center line of sec. 7.</p> <p>Over gently rolling land.</p> <p>8.26 North edge of model plane paved airstrip, bears S. 70° E. and N. 70° W.</p> <p>10.211 The witness point at the intersection of a line between the 1/4 sec. cor. of secs. 7 and 8 and the N 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., with the N-S center line of sec. 7, hereinafter described.</p> <p>20.328 The C-N 1/16 sec. cor. of sec. 7, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the 1990 subdivision of section 7, executed under Group No. 683, with a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.</p> <p>Add the marks 2015 to the brass cap.</p> <p>From this cor., a metal cap, 3 3/4 ins. diam., set in concrete, bears S. 14°38'50" W., 0.259 chs. dist., mkd. NORTH LAS VEGAS SURVEY MONUMENT.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 4, T. 19 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 9, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the 1991 dependent resurvey of a portion of the subdivisional lines, executed under Group No. 697.</p> <p>Add the marks 2015 to the brass cap, and add a collar of stone around the stainless steel post.</p> <p>N. 0°23'30" E., on the N-S center line of sec. 4.</p> <p>Over gently rolling land.</p> <p>39.280 Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and encircled with a collar of stone, with brass cap mkd.</p>
--------	--