

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.50	Powerline, bears S. 89° E. and N. 89° W.
20.328	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.
<p>DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 1, T. 19 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>Reestablishment of the Subdivision of Section 1, Executed by Cadastral Surveyor R.A. Pratt in 1990</p>	
<p>From the 1/4 sec. cor. of secs. 1 and 12, perpetuated by Anthony Zicari, Nevada Professional Land Surveyor No. 11449, in 2004, monumented with a brass tablet, 2 ins. diam., set in concrete, 5 ins. below pavement, in a monument well, mkd. 1/4 S1 S12 VTN PLS 11449, as recorded in Clark County, Nevada, Book 118, Page 53 of Plats. This is accepted as a careful and faithful perpetuation of the position of the 1990 corner.</p>	
<p>from which reference monuments set by Zicari</p>	
<p>An aluminum cap, 2 ins. diam., flush with the concrete of a curb, bears S. 57°34'00" E., 93.6 lks. dist., mkd. VTN RM 61.81 PLS 11449.</p>	
<p>An aluminum cap, 2 ins. diam., flush with the concrete of a curb, bears S. 23°11'20" E., 99.2 lks. dist., mkd. VTN RM 65.45 PLS 11449.</p>	
<p>An aluminum cap, 2 ins. diam., flush with the concrete of a curb, bears S. 20°37'10" W., 102.2 lks. dist., mkd. VTN RM 67.43 PLS 11449.</p>	
<p>An aluminum cap, 2 ins. diam., flush with the concrete of a curb, bears S. 55°01'10" W., 96.7 lks. dist., mkd. VTN RM 63.83 PLS 11449.</p>	
<p>Cor. is located in the intersection of W. Iron Mountain Road, bears E. and W., and N. Bradley Road, bears N. and S.</p>	
<p>From this cor., a brass washer, 2 ins. diam., set in concrete of curb, bears S. 61°31'00" E., 1.045 chs. dist., mkd. CITY OF LAS VEGAS 6LV9012N4.</p>	
<p>N. 0°11'10" W., on the N-S center line of sec. 1.</p>	
<p>Over gently rolling land.</p>	
20.617	The C-S 1/16 sec. cor. of sec. 1, determined by Kurt F. Orban, Nevada Professional Land Surveyor No. 17828, in 2007, monumented with a rebar, 3/4 in. diam., 18 ins. long, with aluminum cap, 3 1/4 ins. diam., firmly set, 6 ins. below the ground, mkd. G.C. WALLACE INC C S1/16 S1 C PLS 17828 2003, as recorded in Clark County, Nevada, File 165, Page 48 of Surveys. This is accepted as a careful and faithful determination of the position of the corner.