

DEPENDENT RESURVEY OF A PORTION OF THE
 SUBDIVISION OF SECTION 24,
 T. 19 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of the Survey Executed by Cadastral Surveyor Ronald E. Williams in 1991.</p> <hr style="width: 20%; margin: auto;"/> <p>Beginning at the center 1/4 sec. cor. of sec. 24, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the surface of the ground, with brass cap mkd. as described in the field notes of the 1991 subdivision of section 24, T. 19 S., R. 61 E., executed under Group No. 697.</p> <p>from which accessories established by Larry E. Crow, Nevada Professional Land Surveyor No. 9399, in 1992, as recorded in Clark County, Nevada, corner record 19920521-0000720, sheet 9</p> <p style="padding-left: 40px;">An aluminum cap, 2 ins. diam., firmly set in concrete base, flush with the surface of the ground, mkd. NORTH LAS VEGAS SURVEY MONUMENT RM 81.36 PLS 9399, bears N. 48°27'00" E., 123.3 lks. dist.</p> <p style="padding-left: 40px;">An aluminum cap, 2 ins. diam., firmly set in concrete base, flush with the surface of the ground, mkd. NORTH LAS VEGAS SURVEY MONUMENT RM 89.89 PLS 9399, bears S. 38°11'00" E., 136.2 lks. dist.</p> <p style="padding-left: 40px;">An aluminum cap, 2 ins. diam., firmly set in concrete base, flush with the surface of the ground, mkd. NORTH LAS VEGAS SURVEY MONUMENT RM 97.63 PLS 9399, bears S. 48°29'50" W., 147.9 lks. dist.</p> <p style="padding-left: 40px;">An aluminum cap, 2 ins. diam., firmly set in concrete base, flush with the surface of the ground, mkd. NORTH LAS VEGAS SURVEY MONUMENT RM 76.55 PLS 9399, bears N. 38°10'00" W., 116.0 lks. dist.</p> <p>N. 0°12'30" E., on the N-S center line of sec. 24.</p> <p>20.310 The C-N 1/16 sec. cor. of sec. 24, determined by Allen L. Hagen, Nevada Professional Land Surveyor No. 7755, in 1997, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 1 in. above the surface of the ground, with aluminum cap mkd. A.L. HAGEN PLS 7755, as recorded in Clark County, Nevada, File 89, Page 3, of Surveys, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>N 1/16 S24</p> <p>C</p> </div> <p style="text-align: center;">2017</p>
--------	--