DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 19 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	A rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap, mkd. NORTH LAS VEGAS S T S R6 E RM 66.22 PLS 9399 SURVEY
	MONUMENT, bears S. 44°58'50" W., 100.3 lks. dist.
	Cor. is located 2.3 lks. S. of fence, bears E. and W.
	S. 88°28'30" W., beginning new measurement.
20.408	The W 1/16 sec. cor. of secs. 17 and 20, determined by Allen L. Hagen, Nevada Professional Land Surveyor No. 7755, in 1997, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. A.L. HAGEN PLS 7755, as recorded in Clark County, Nevada, File 89, Page 3, of Surveys, and is accepted as a careful and faithful determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	W 1/16 $\frac{\text{S17}}{\text{S20}}$ 2017
	Insert the rebar inside the stainless steel post.
	Cor. is located 1.8 lks. S. of fence, bears E. and W.
	From this corner, a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, in the center of an aerial photo target, with aluminum cap mkd. GCW CONTROL, bears S. 13°34'10" W., 0.736 chs. dist.
	S. 88°28'30" W., beginning new measurement.
18.46	Gate in fence, bears N. and S.
20.408	The cor. of secs. 17, 18, 19 and 20.
	SUBDIVISION OF SECTION 20, T. 19 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 20 and 29.
	N. 0°08'50" E., on the N-S center line of sec. 20.
20.494	The center S 1/16 sec. cor. of sec. 20, determined by Allen L. Hagen, Nevada Professional Land Surveyor No. 7755, in 1997, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd.
1	