

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor A.J. Hatch in 1867, and a Portion of the Dependent Resurvey Executed by Associate Cadastral Engineer C.S. Swanholm and Assistant Cadastral Engineer J.W. Hardison in 1942</p> <hr/>
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>S. 89°23'00" W., bet. secs. 13 and 24.</p>
17.05	<p>Dirt road, 25 lks. wide, bears N. 20° E. and S. 20° W.</p>
41.58	<p>Powerline, bears N. and S.</p>
41.835	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R19E S13 1/4 — S24</p>
	<p style="text-align: center;">2017</p>
	<p>from which</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 30°24'00" E., 145.5 lks. dist., with brass cap mkd. RM T21N R19E 1/4 S13 96.0 FT TO COR 2017 and an arrow pointing to the corner.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 51°01'00" W., 143.0 lks. dist., with brass cap mkd. RM T21N R19E 1/4 S13 94.4 FT TO COR 2017 and an arrow pointing to the corner.</p>
	<p>Point located in an intersection of dirt roads, 20 lks. wide, extending N., E., S. and W.</p>
	<p>From this point, a position determined by person(s) unknown, bears N. 41°50'10" E., 0.402 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set flush with the ground. Not utilized during the course of this survey.</p>