

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S 2 E 1/16 ——— S11 2017
	Insert the rebar within the stainless steel post and leave the steel fence post in place.
	<hr/> N. 88°18'50" W., beginning new measurement.
10.560	From this point, a wood post, 3 ins. diam., firmly set, projecting 3 ft. above the ground, no visible marks, with a mound of stone, 4 ft. diam., 1 ft. high, N. of post, bears N., 1.433 chs. dist. Not utilized during the course of this survey.
11.62	Trail road, 10 lks. wide, bears N. 60° E. and S. 60° W., in bottom of drainage, drains S. 60° W.
19.702	The 1/4 sec. cor. of secs. 2 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above an embedded mound of stone, 3 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 21 N., R. 19 E., executed under Group No. 312, with a steel fence post firmly set alongside.
	from which the 1942 bearing trees
	A juniper, 7 ins. diam., bears N. 18 1/2° E., 57.0 lks. dist., with partially healed blaze, the marks S2 BT visible.
	A juniper, 10 ins. diam., bears S. 58° W., 81.0 lks. dist., with open blaze mkd. 1/4 S11 BT.
	<hr/> SUBDIVISION OF SECTION 2, T. 21 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 2 and 11.
	N. 1°44'20" E., on the N-S center line of sec. 2.
40.880	Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.