

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 22 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor A.J Hatch in 1867, a Portion of the Retracement Executed by U.S. Transitman A.T. Harris in 1914, and a Portion of the Dependent Resurvey Executed by Associate Cadastral Engineer C.S. Swanholm and Assistant Cadastral Engineer J.W. Hardison in 1942</p> <hr/>
	<p>Beginning at the cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the N. bdy. of T. 21 N., R. 19 E., executed under Group No. 312, with an embedded mound of stone, 3 ft. diam., E. of cor.</p>
	<p>from which the 1942 bearing tree</p>
	<p>A juniper, 11 ins. diam., bears N. 75 1/2° W., 137.0 lks. dist., with mostly healed blaze, illegible marks.</p>
	<p>From this cor., a corner of fences bears N. 28°56'40" W., 0.028 chs. dist., cable fences extend N. and W.</p>
	<p>N. 89°48'40" W., bet. secs. 2 and 35.</p>
<p>3.10</p>	<p>Small spur, slopes S.</p>
<p>20.083</p>	<p>Point for the E 1/16 sec. cor. of secs. 2 and 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">S35 E 1/16 ————— S 2</p>
	<p style="text-align: center;">2017</p>
	<p>Point located 15 ft. southerly of cable fence, bears E. and W.</p>
<p>30.80</p>	<p>Spur, slopes N. 30° E</p>
<p>40.166</p>	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above a mound of stone, 6 ft. diam., 3 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the N. bdy. of T. 21 N., R. 19 E., executed under Group No. 312.</p>
	<p>from which the remaining 1942 bearing tree</p>