

SUBDIVISION OF SECTION 26,  
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0°03'30" E., on the N-S center line of sec. 26.</p>
22.98	Trail road, 10 lks. wide, bears N. 75° E. and S. 35° W.
40.174	<p>Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T22N R20E C 1/4 S26</p> <p style="text-align: center;">2017</p>
60.098	<p>Point for the C-N 1/16 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16   S26 C</p> <p style="text-align: center;">2017</p>
80.022	<p>The 1/4 sec. cor. of secs. 23 and 26.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26, reestablished by Thomas A. Foote, Nevada Registered Land Surveyor No. 3736, in 1972-1976, monumented with a rebar, 5/8 ins. diam., 12 ins. long, firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. 1/4 25 26 LS3736, as shown on Survey Map No. 985, filed in Washoe County, Nevada, with a stake, 3/4 ins. diam., firmly set alongside, projecting 5 ins. above the ground, and with a granite stone, 16x9x8 ins., lying loose alongside, mkd. 1/4 on a face. This is accepted as a careful and faithful reestablishment of the position of the 1906 corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>