DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor G.W. Garside in 1873 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor R.A. Pratt in 1988-1991
	From the cor. of Tps. 41 N., 41 1/2 N. and 42 N., Rs. 25 and 26 E., hereinbefore described.
	NORTH, bet. secs. 31 and 36.
	Over rolling land, through scattered sagebrush and native grass on the SW. side of Summit Lake.
0.01	Barbed wire fence, bears E. and W.
7.120	The 1988-1991 meander cor. of secs. 31 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush in a mound of stone, 2 1/2 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 42 N., R. 25 E., executed under Group No. 655.
	Set a galvanized steel fence post, 6 ft. long, 2 ft. in the ground, alongside the stainless steel post with a BLM Land Survey Monument sign attached.
12.70	Enter water of Summit Lake.
20.000	Point for the S 1/16 sec. cor. of secs. 31 and 36, falls in Summit Lake.
33.100	The point for the 1873 meander cor. of secs. 31 and 36, falls in Summit Lake.
	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor G.W. Garside in 1873 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor R.A. Pratt in 1988-1991
į	From the cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°06'40" W., bet. secs. 35 and 36.
	Over rolling land, through scattered sagebrush and native grass.
41.537	The 1/4 sec. cor. of secs. 35 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 42 N., R. 25 E., executed under Group No. 655, with a steel fence post alongside, and with a mound of stone, 2 1/2 ft. diam., 1 ft. high, W. of cor.