

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>42.559</p>	<p>Set a galvanized steel fence post, 6 ft. long, 2 ft. in the ground, alongside the stainless steel post with a BLM Land Survey Monument sign attached.</p> <hr/> <p>S. 89°59'40" W., beginning new measurement.</p> <p>The cor. of secs. 25, 26, 35, and 36.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE 1873 MEANDER LINES OF SUMMIT LAKE, T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor G.W. Garside in 1873 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor R.A. Pratt in 1988-1991</p> <hr/> <p>From the point for the 1873 meander cor. of secs. 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>Thence, with the adjusted 1873 meanders of Summit Lake in sec. 36.</p> <p>N. 33°42'00" W., 12.530 chs. At 10.075 chs., point for the special meander cor. at intersection with the E-W center line of sec. 36, hereinafter described.</p> <p>N. 23°56'00" W., 38.880 chs. At 20.729 chs., point for the special meander cor. at intersection with the E-W center line of the NE 1/4 of sec. 36, hereinafter described.</p> <p>At 33.492 chs., point for the special meander cor. at intersection with the N-S center line of the NE 1/4 of sec. 36, hereinafter described.</p> <p>N. 28°46'00" E. 5.02 chs. At 2.60 chs., barbed wire fence, bears E. and W.</p> <p>The 1873 meander cor. of secs. 25 and 36, hereinbefore described.</p> <hr/>
-----------------------------	---