

TOWNSHIP 29 SOUTH, RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The NAD 1983 (2011) (EPOCH:2010.0000) geographic position, of the following corners were determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) AZGV GOLDEN VALLEY CORS ARP, NVLA LAUGHLIN CORS ARP, AZDS DOLAN SPRINGS CORS ARP, and carried forward by RTK observations.</p> <p>The standard 1/4 sec. cor. of sec. 34, T. 28 S., R. 63 E. is as follows:</p> <p style="padding-left: 40px;">Latitude: 35°27'27.695" N. Longitude: 114°55'38.424" W.</p> <p>The cor. of secs. 11, 12, 13, and 14 is as follows:</p> <p style="padding-left: 40px;">Latitude: 35°25'44.358" N. Longitude: 114°54'15.654" W.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL SOUTH THROUGH A PORTION OF RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">REESTABLISHMENT OF A PORTION OF THE SURVEY EXECUTED BY U.S. Deputy Surveyor W.H. Myrick in 1883 and a Portion of the Dependent Resurvey Executed by Surveyor J.W. Hardison and Public Land Surveyors W. McConkie and A.C. Alberga in 1939-40</p> <hr/> <p>From the standard cor. of secs. 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above the surface of the ground, in a mound of stone, 3 1/2 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the 1939-40 dependent resurvey of the Seventh Standard Parallel South, through Range 63 East, executed under Group No. 239.</p> <p>N. 89°41'30" W., on the S. bdy. of sec. 35.</p> <p>16.395 The closing cor. of secs. 1 and 2, T. 29 S., R. 63 E., hereinafter described.</p> <p>22.80 Wash, 30 lks. wide, 3 ft. deep, drains SE.</p> <p>25.50 Wash, 30 lks. wide, drains SE.</p> <p>26.20 Corner of barbed wire fences, extending S. and W.</p> <p>35.40 Corner of barbed wire fences, extending E. and SSW.</p> <p>36.013 The E 1/16 sec. cor. of sec. 2 only, T. 29 S., R. 63 E., determined by William Avery, Nevada Professional Land Surveyor No. 5571, monumented with a rebar, 5/8 in. diam., firmly set, 1 in. below the surface of the ground, with aluminum cap mkd. PLS 5571, no record found, and is accepted as a careful and faithful determination of the position of the corner.</p>
--------	--