

DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL SOUTH
THROUGH A PORTION OF RANGE 63 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
25.778	Intersect line 3-4, Mineral Survey No. 2366, Ella lode, intersection point, hereinafter described, at a point from which Cor. No. 3, hereinafter described, bears N. 26°32'10" E., 2.897 chs. dist.						
39.663	The standard cor. of secs. 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 19 ins. above the surface of the ground, in a mound of stone, 3 1/2 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the 1939-40 dependent resurvey of the Seventh Standard Parallel South, through Range 63 East, executed under Group No. 239.						
	S. 89°42'40" W., on the S. bdy. of sec. 34.						
15.562	The closing cor. of secs. 2 and 3, T. 29 S., R. 63 E., hereinafter described.						
39.377	The standard 1/4 sec. cor. of sec. 34, perpetuated by Robin D. Rasmussen, Nevada Professional Land Surveyor No. 8697, in 1994, monumented with an aluminum post, 2 1/4 ins. diam., firmly set, projecting 4 ins. above the surface of the ground, with aluminum cap mkd. SC T28S R63E 1/4 S 34 PLS 8697 1994, as recorded in Clark County, Nevada, File 91, Page 89, of Surveys, with a mound of stone, 3 ft. diam., 1 ft. high, NW. of cor. This is accepted as a careful and faithful perpetuation of the reestablished 1939-40 resurvey corner.						
	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 29 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA						
	Reestablishment of a Portion of the Survey executed by U.S. Deputy Surveyor W.H. Myrick in 1883						
	From the cor. of secs. 11, 12, 13, and 14, monumented with a basalt stone, 13x13x9 ins. (Record: 19x13x9 ins.), firmly set, projecting 11 ins. above the surface of the ground, mkd. with 4 grooves on the S. face and 1 notch on the E. edge.						
	At the corner point						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.						
	<table> <tr> <td>T29S</td><td>R63E</td></tr> <tr> <td>S11</td><td>S12</td></tr> <tr> <td>S14</td><td>S13</td></tr> </table>	T29S	R63E	S11	S12	S14	S13
T29S	R63E						
S11	S12						
S14	S13						
	2018						
	Bury the original corner stone alongside the stainless steel post.						