

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 17 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T17S R59E S31 1/4 — S 6 T18S 2015</p> <hr/> <p>S. 89°41'30" W., beginning new measurement.</p> <p>32.220 The witness point, at the intersection of the easterly right-of-way line of U.S. Highway No. 95, with the S. bdy. of the Tp., hereinafter described.</p> <p>37.40 Northbound lane, U.S. Highway No. 95, bears S. 25° E. and N. 25° W.</p> <p>39.20 Southbound lane, U.S. Highway No. 95, bears S. 25° E. and N. 25° W.</p> <p>40.686 The cor. of Tps. 17 and 18 S., Rs. 58 and 59 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush in a mound of stone, 3 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 17 S., R. 58 E., executed concurrently under this same Group, with a steel fence post firmly set alongside.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 17 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors R.H. Woods and W.H. Myrick in 1882</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an iron pipe, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, and in a collar of stone, with brass cap mkd. as described in the dependent resurvey of a portion of the N. bdy., T. 18 S., R. 59 E., executed under Group No. 881.</p> <p>N. 1°27'30" W., bet. secs. 32 and 33.</p> <p>8.80 Landy Street, gravel surface, 20 lks. wide, bears S. 35° E. and N. 35° W.</p> <p>9.30 Fence brace, continue along barbed wire fence.</p> <p>33.00 Fence brace, end of barbed wire fence.</p> <p>33.70 Corn Creek Road, gravel surface, 45 lks. wide, bears N. 75° E. and S. 75° W.</p>
--------	--