

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 17 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T17S R58E S36 1/4 — S 1 T18S 2015</p> <p>Bury mkd. stone alongside stainless steel post.</p> <hr/> <p>S. 89°02'10" W., beginning new measurement.</p> <p>39.172 The cor. of secs. 1, 2, 35 and 36, monumented with a limestone, 14x9x7 ins. (Record: 18x11x9 ins.), loosely set, projecting 8 ins. above a mound of stone, 4 ft. diam., 1/2 ft. high, mkd. with 1 groove on E. face and 5 grooves on W. face, with a nail in a wood hub set beneath.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17S R58E S35 S36 — — S 2 S 1 T18S 2015</p> <p>Bury mkd. stone alongside stainless steel post.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 17 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.A. Carter in 1881</p> <hr/> <p>From the cor. of Tps. 17 and 18 S., Rs. 58 and 59 E., hereinbefore described.</p> <p>N. 0°25'30" W., bet. secs. 31 and 36.</p> <p>3.20 Southbound lane, U.S. Highway No. 95, bears S. 25° E. and N. 25° W.</p> <p>7.20 Northbound lane, U.S. Highway No. 95, bears S. 25° E. and N. 25° W.</p> <p>16.641 The witness point, at the intersection of the easterly right-of-way line of U.S. Highway No. 95, with the line bet. secs. 31 and 36, hereinafter described.</p>
--------	--