## DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 7,

## T. 15 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA CHAINS Reestablishment of Portions of the Further Subdivision of Section 7 Executed by Cadastral Surveyor C. Gil Mendoza in 2016 Beginning at the point for the C-S-S-NE-NE 1/1024 sec. cor. of sec. 7, at its computed position, as determined in the 2016 further subdivision of section 7, executed under Group No. 966. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. 1/1024 2018 Cor. is located on S. facing slope. From this point, the SW-SE-NE-NE 1/1024 sec. cor. of sec. 7, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the surface of the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the 2016 further subdivision of section 7, T. 15 S., R. 66 E., executed under Group No. 966, bears N. 89°15'40" E., 2.512 chs. dist. S. $89^{\circ}15'40"$ W., on a portion of the computed E-W center line of the SE1/4SW1/4NE1/4NE1/4 of sec. 7. 4.275 Point for a witness point on the E-W center line of the SE1/4SW1/4NE1/4NE1/4 of sec. 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. T15S R66E S-S-N-N - S-S-N-N 2018 Cor. is located on S. facing slope. 4.713 The witness point on the E-W center line of the SE1/4SW1/4NE1/4NE1/4 of sec. 7, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the surface of the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the 2016 further subdivision of section 7, T. 15 S., R. 66 E., executed under Group No. 966.