

DEPENDENT RESURVEY OF PORTIONS OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 7,
T. 15 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the point for the C-N-SW-NE-NE 1/1024 sec. cor. of sec. 7, at its computed position, as determined in the 2016 further subdivision of section 7, executed under Group No. 966.</p> <p>POINT NOT MONUMENTED</p> <p>S. 89°02'50" W., on a portion of the computed E-W center line of the NW1/4SW1/4NE1/4NE1/4 of sec. 7.</p> <p>1.255 Point for the C-E-NW-SW-NE-NE 1/4096 sec. cor. of sec. 7, at its computed position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">1/4096</p> <p style="text-align: center;">2018</p> <p>Cor. is located on N. facing slope.</p> <p>2.510 Point for the NW-SW-NE-NE 1/1024 sec. cor. of sec. 7, at intersection with the computed N-S center line of the NW1/4SW1/4NE1/4NE1/4.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, the C-N-S-N-NE 1/1024 sec. cor. of sec. 7, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the surface of the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the 2016 dependent resurvey of portions of the subdivision-of-section lines of section 7, T. 15 S., R. 66 E., executed under Group No. 966, bears S. 89°02'50" W., 2.510 chs. dist.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE METES-AND-BOUNDS SURVEY IN SECTION 7, T. 15 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Metes-and-Bounds Survey Executed by Cadastral Surveyor C. Gil Mendoza in 2016</p> <hr/> <p>From the witness point on the E-W center line of the SE1/4SW1/4NE1/4NE1/4 of sec. 7, hereinbefore described.</p> <p>N. 15°41'50" E., on course adjacent to fence line, in sec. 7.</p> <p>0.413 Point for a witness point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
--------	---