

DEPENDENT RESURVEY OF A PORTION OF THE
METES-AND-BOUNDS SURVEY IN SECTION 7,
T. 15 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.781	<div data-bbox="878 285 1024 513" data-label="Diagram"> </div> <p>Cor. is located in barbed wire fence, bears NNE. and SSW.</p> <p>Angle Point No. 2, in sec. 7, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the surface of the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the 2016 metes-and-bounds survey in section 7, T. 15 S., R. 66 E., executed under Group No. 966.</p>
1.074	<hr/> <p>THE FURTHER SUBDIVISION OF SECTION 7, T. 15 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the point for the SW-NE-NE 1/256 sec. cor. of sec. 7, at intersection with the computed E-W center line of the SW1/4NE1/4NE1/4, as determined in the 2016 further subdivision of section 7, executed under Group No. 966.</p> <p>POINT NOT MONUMENTED</p> <p>N. 0°29'40" W., on a portion of the computed N-S center line of the SW1/4NE1/4NE1/4 of sec. 7.</p> <p>Point for a witness point on the N-S center line of the SW1/4NE1/4NE1/4 of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
1.325	<div data-bbox="878 1396 1024 1680" data-label="Diagram"> </div> <p>Cor. is located in barbed wire fence, bears NE. and SW.</p> <p>Point for the C-S-N-SW-NE-NE 1/4096 sec. cor. of sec. 7, at its computed position.</p>